

CRC-611

SECTION VI - REACTIVITY AND STA	ABILITY DATA		
STABILITY UNSTABLE			
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens.			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide			
		CONDITIONS TO	AVOID
POLYMERIZATION WI	LL NOT OCCUR X		None
SECTION VII - HEALTH HAZARD DATA			
ROUTES OF ENTRY INHALATION? Yes SKIN? Yes INGESTION? Yes EYES? Yes			
HEALTH ACUTE X See Signs and Symptoms of Exposure below.			
HAZARDS CHRONIC X Brain and Nervous System Damage (Referred to as solvents or painters syndrome). Drying or Cracking skin.			
CARCINOGENICITY: IARC 2B			
Grove AND			
SIGNS AND SYMPTOMS OF Hea	Handacha Digginase Decusinese Estinus Irragular Handback Skin and Eur Irritation		
SYMPTOMS OF Headache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation. EXPOSURE Target Organs: CNS, CVS, PNS, Liver, Kidneys, Lungs, Respiratory System, Skin.			
Target Organs: CNS, CVS, PNS, Liver, Kluneys, Lungs, Respiratory System, Skin.			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Pre-existing Heart, Liver, Kidney and Lung disorders.			
INEDICAL COMPITIONS GENERALD AGGRAVATED BY EAR OSORE TIC-CAISING HEAR, LIVE, KIUREY and Lung UISUICES.			
EMERGENCY AND Ingestion: Contact Physician or Poison Control Immediately.			
	Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary.		
PROCEDURES Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician.			
Skin: Wash with soap and water.			
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE			
STEPS TO BE TAKEN Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers.			
IN CASE MATERIAL IS Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material to dam			
RELEASED OR SPILLED or contain spills. If large spill, notify appropriate state and local agencies.			
WASTE DISPOSAL METHODS Dispose of product in accordance with local, county, state and federal regulations.			
NNG 1777019 70 N			
PRECAUTIONS TO BE Keep away from sparks, flame and heat sources. Do not store above 120°F and use adequate ventilation.			
TAKEN IN HANDLING Avoid inhalation of vapors and contact with liquid product. Use good personal hygiene. AND STORAGE			
ANDSTORAGE			
OTHER Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally safe manner			
PRECAUTIONS in accordance with Governmental Regulations.			
SECTION IX - CONTROL MEASURES			
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airborne concentration, PROTECTIVE GLOVES			
use a Respirator with appropriate NIOSH ap			Impervious Gloves
VENTILATION LOCAL EXHAUST Supplemental (if needed)			SPECIAL None
MECHANICAL (GENERAL) To maintain exposure be		elow PEL's	OTHER None
EYE PROTECTION	EYE PROTECTION		OTHER PROTECTIVE CLOTHING OR EQUIPMENT
Chemical splash goggles, or approved eye protection.			Chemcial Apron/Eye bath/Safety Shower
WORK HYGIENIC PRACTICES Wash thoroughly after handling.			
SECTION X - TRANSPORTATION INFORMATION (Optional)			
DOT PROPER SHIPPING NAME Coating Solution DOT HAZARD CLASS 3			
DOT UN NUMBER UN1139		DOT PACKING GROUP II	
IATA PROPER SHIPPING NAME Coating Solution		IATA HAZARD CLASS 3	
IATA UN NUMBER UN 1139 IATA PACKING GROUP II			
SECTION XI - 313 SUPPLIER NOTIFICATION			
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE			
1)	MUNITY RIGHT -TO-KNOW AC	T OF 1986, 40 CFR	372, (see table on page 1 for CAS # and percent by weight).
Hexane, Xylene, and Ethylbenzene			
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH			
DEFECTS, OR OTHER REPRODUCTIVE HARM.			

01/09 Page 2.