

---

**Product: DFP**  
**Dissipative Fluted Plastic**  
 Typical Physical Properties

---

Property	Unit	ASTM	Value
<b>1.0 Physical</b>			
Hardness	Shore-D	D-2240	69
Melt Flow	g/10 min	D-1238	1.0
Specific Gravity	---	D-792	0.92
<b>2.0 Mechanical</b>			
Tensile Strength	psi	D-638	3,5000
Flexural Modules	psi	D-638	160,000
Izod Impact	ft-lb/in	D-256	2.2
<b>3.0 Thermal</b>			
HDT @ 66 psi	F	D648	212
<b>4.0 Thermal</b>			
Surface Resistivity	ohms/sq	---	10 <sup>6</sup> to 10 <sup>9</sup>

---

Warranty

Conductive Containers, Inc. guarantees CORSTAT™ to be free from defects in material and workmanship. Specifications and technical information presented are based on testing methods believed to produce accurate results. Conductive Containers, Inc.'s only obligation will be to replace or repair any CORSTAT™ products proved to be defective at time of shipment. Conductive Containers, Inc. will not be liable for any injury, loss or damage direct or consequential, arising out of the use or the inability to use the products. Before using, user shall determine the suitability of the product for the intended use, and user shall assume risk and liability in connection herewith.