

MFG TRAY INSERTS

STANDARD SOLUTIONS

PART #

2416 SM

PART #

CTL-4-1175-TPU

CTL-15-4843-TPU

CCI uses the durable conductive MFG tray as a format to provide clean static-safe solutions for handling sensitive electronics.

MFG TRAYS-

- Conductive MFG tray only
- Fits all part numbers listed below

PART #	DESCRIPTION
2416 MFG	24-1/4 x 16-1/8 x 1-14" ID

DESCRIPTION

SafeMat 24-1/4 x 16-1/8"

DESCRIPTION

4 cavity KSF thermofomed insert

11 x 7-1/2 x 1" cavities

15 cavity KSF thermofomed insert

4-4/5 x 4-1/3 x 1" cavities

4-4/5 x 4-1/3 x 1" cavities

SAFEMAT-

- FOD-free, permanent dissipative mat
- IPA cleanable won't use static properties

PERMANENT FOAMS

• Dissipative and conductive crosslink foam pads

PART #	DESCRIPTION
2416-30D	Dissipative Xlink 24-1/4 x 16-1/8"
2416-32C	Conductive Xlink 24-1/4 x 16-1/8"

KLEANSTAT INSERTS

- Thermoformed cavities to fit your application
- Low-FOD flexible and safe
 KSF material

IDP INSERTS -

- Dissipative thermoformed cavities to fit
- Choose from standard layouts or custom

PART #	DESCRIPTION
CTL-4-1175-680	4 cavity S680 thermofomed insert 11 x 7-1/2 x 1" cavities
CTL-15-4843-680	15 cavity S680 thermofomed insert

KLEANSTAT BUBBLE INSERTS


- The ultimate permanently dissipative FOD-free cushioning for handling sensitive electronics
- Flexible TPU dissipative bubble
- IPA Cleanable

Small Bubble Inserts

PART #	DESCRIPTION
KSB2416-SB-15-TPU	24-1/4 x 16-1/8 x .015 Sm Bubble
KSB2416-SB-25-TPU	24-1/4 x 16-1/8 x .025 Sm Bubble

Medium Bubble Inserts

PART #	DESCRIPTION
KSB2416-MB-15-TPU	24-1/4 x 16-1/8 x .015 Med Bubble
KSB2416-MB-25-TPU	24-1/4 x 16-1/8 x .025 Med Bubble



Large Bubble Inserts

PART #	DESCRIPTION
KSB2416-LB-40-TPU	24-1/4 x 16-1/8 x .040 Lg Bubble

Flat KSF Inserts

PART #	DESCRIPTION
KSF2416-25-TPU	24-1/4 x 16-1/8 x .025 Flat Pad
KSF2416-40-TPU	24-1/4 x 16-1/8 x .040 Flat Pad

See opposite side for engineered custom solutions and insert drawings.

Questions? Call us today and talk to one of our experts. If you can dream it - CCI can make it a reality.









MFG TRAY INSERTS


Choose one of these standard designs in any quantity and utilize the CCI rigid conductive, static dissipative or TPU soft static dissipative material of your choice.

4-CAVITY TRAY





15-CAVITY TRAY



DESIGN-YOUR-OWN TRAY

HIGH-TEMPCUSTOM SOLUTIONS

- CCI stocks conductive plastic for use in temperatures up to 275°F
- Give us your tray design requirements for the perfect solution

Talk to a CCI representative about your custom handling need. We will help you use our master tool to create the cavity size you need in the material type you prefer. Give us the cavity size desired and we will create the correct design. Custom designs require an engineering fee.

